

XB9 5 joule xenon beacon range

Ex d, weatherproof



Overview

These compact and lightweight beacons have been designed for use in potentially explosive atmospheres and harsh environmental conditions. The beacon housing, including the flamepaths, is manufactured completely from a UV stable glass reinforced polyester which is ideally suited for use offshore and onshore.

Stainless steel screws and mounting bracket are incorporated ensuring a totally corrosion free unit.

Units can be painted to customer specification and supplied with identification labels.

Features

- Zone 1 and Zone 2 use
- Ex d IIC T5/T6
- ATEX approved, Ex II 2G
- IECEx certified Gb
- IP66 and IP67
- Certified temperature -55°C to $+55^{\circ}\text{C}$
- Corrosion Free GRP
- Various lens colours
- Lens guard fitted as standard
- Optional gland plus cable tail
- Stainless steel mounting bracket & screws
- Replaceable tube



Certifications

ATEX Ex d Cert. no. Baseefa BAS00ATEX2031
 Certified to: EN60079-0, EN60079-1
 Ex II 2G, Ex d IIC T5/T6 Gb

IECEX Ex d Cert. no. IECEX BAS 10.0113
 Certified to: IEC60079-0, IEC60079-1
 Ex d IIC T5/T6 Gb

Specifications

Material	Body & cover: glass reinforced polyester (GRP) Lens: glass Cover screws & bracket: stainless steel 316
Finish	Natural black or painted to customer specification
Weight	1.6kg
Certified temp	-55°C to +40°C (T6). -55°C to +55°C (T5)
Ingress protection	IP66 & IP67
Fire retardancy	GRP is fire retardant to IEC 60695-11-10
Terminals	3 x 2.5mm ²
Mounting	Wall mounted via bracket
Entries	1 x M20 or PG 13.5
Optional	1 x 3m cable tail and gland
Tube life	>1x10 ⁶ flashes

Electrical ratings:

Voltage	d.c				a.c.	
	12	24	48	60	110	240/254
Tube energy (J)	5	5	5	5	5	5
Current (A)	0.65	0.35	0.18	0.13	0.08	0.06/0.057
Effective intensity (Cd)	29	29	29	29	29	29
Peak intensity (Cd)	22213	22213	22213	22213	22213	22213
Power consumption (W)	8	9	9	8	9	15

Note: The above figures (Cd) are for a clear lens @ 1Hz flash rate

Multiplying factor for coloured lenses:

Red	Blue	Amber	Green	Yellow
0.15	0.12	0.51	0.49	0.86

The photometric data has been verified by BSI. A report is available if required

Ordering requirements

The following code is designed to help in selection of the correct unit. Build up the reference number by inserting the code for each component into the appropriate box

Model	Certification	Voltage	Flashrate	Lens	Lens guard	Tag/duty	Entries/cable tail	Finish																																																																												
XB9																																																																																				
	<table border="1"> <thead> <tr> <th>Certification</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Uncertified</td> <td>W</td> </tr> <tr> <td>ATEX</td> <td>D</td> </tr> <tr> <td>IECEX</td> <td>J</td> </tr> </tbody> </table>	Certification	Code	Uncertified	W	ATEX	D	IECEX	J	<table border="1"> <thead> <tr> <th>Voltage</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>12Vdc</td> <td>012</td> </tr> <tr> <td>24Vdc</td> <td>024</td> </tr> <tr> <td>48Vdc</td> <td>048</td> </tr> <tr> <td>60Vdc</td> <td>060</td> </tr> <tr> <td>110Vac</td> <td>110</td> </tr> <tr> <td>240Vac</td> <td>240</td> </tr> <tr> <td>254Vac</td> <td>254</td> </tr> </tbody> </table>	Voltage	Code	12Vdc	012	24Vdc	024	48Vdc	048	60Vdc	060	110Vac	110	240Vac	240	254Vac	254	<table border="1"> <thead> <tr> <th>Flash rate</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>60 / min</td> <td>06</td> </tr> </tbody> </table> <p>Other flash rates available on request, please specify</p>	Flash rate	Code	60 / min	06	<table border="1"> <thead> <tr> <th>Colour</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Red</td> <td>R</td> </tr> <tr> <td>Blue</td> <td>B</td> </tr> <tr> <td>Green</td> <td>G</td> </tr> <tr> <td>Amber</td> <td>A</td> </tr> <tr> <td>Yellow</td> <td>Y</td> </tr> <tr> <td>Clear</td> <td>C</td> </tr> </tbody> </table>	Colour	Code	Red	R	Blue	B	Green	G	Amber	A	Yellow	Y	Clear	C	<table border="1"> <thead> <tr> <th>Guard</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Yes</td> <td>Y</td> </tr> </tbody> </table>	Guard	Code	Yes	Y	<table border="1"> <thead> <tr> <th>Label</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>None</td> <td>N</td> </tr> <tr> <td>Yes</td> <td>Y*</td> </tr> </tbody> </table> <p>*Please specify</p>	Label	Code	None	N	Yes	Y*	<table border="1"> <thead> <tr> <th>Entries</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>1 x M20</td> <td>1B</td> </tr> <tr> <td>1 x PG 13.5</td> <td>1P</td> </tr> <tr> <td>Cable & tail 3m cable</td> <td>CB</td> </tr> </tbody> </table>	Entries	Code	1 x M20	1B	1 x PG 13.5	1P	Cable & tail 3m cable	CB	<table border="1"> <thead> <tr> <th>Finish</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Natural black</td> <td>N</td> </tr> <tr> <td>Red</td> <td>R</td> </tr> <tr> <td>Blue</td> <td>B</td> </tr> <tr> <td>Yellow</td> <td>Y</td> </tr> <tr> <td>Grey</td> <td>G</td> </tr> <tr> <td>White</td> <td>W</td> </tr> <tr> <td>Special</td> <td>S*</td> </tr> </tbody> </table> <p>*Please specify</p>	Finish	Code	Natural black	N	Red	R	Blue	B	Yellow	Y	Grey	G	White	W	Special	S*
Certification	Code																																																																																			
Uncertified	W																																																																																			
ATEX	D																																																																																			
IECEX	J																																																																																			
Voltage	Code																																																																																			
12Vdc	012																																																																																			
24Vdc	024																																																																																			
48Vdc	048																																																																																			
60Vdc	060																																																																																			
110Vac	110																																																																																			
240Vac	240																																																																																			
254Vac	254																																																																																			
Flash rate	Code																																																																																			
60 / min	06																																																																																			
Colour	Code																																																																																			
Red	R																																																																																			
Blue	B																																																																																			
Green	G																																																																																			
Amber	A																																																																																			
Yellow	Y																																																																																			
Clear	C																																																																																			
Guard	Code																																																																																			
Yes	Y																																																																																			
Label	Code																																																																																			
None	N																																																																																			
Yes	Y*																																																																																			
Entries	Code																																																																																			
1 x M20	1B																																																																																			
1 x PG 13.5	1P																																																																																			
Cable & tail 3m cable	CB																																																																																			
Finish	Code																																																																																			
Natural black	N																																																																																			
Red	R																																																																																			
Blue	B																																																																																			
Yellow	Y																																																																																			
Grey	G																																																																																			
White	W																																																																																			
Special	S*																																																																																			

General arrangement drawing (all dimensions in mm)

